


UM980

GPS/BDS/GLONASS/Galileo/QZSS
All-constellation Multi-frequency High
Precision RTK Positioning Module



17.0 × 22.0 × 2.6 mm

Applications



Surveying and Mapping



Lawn Mower



Precision Agriculture



UAV

Physical Characteristics

Packaging	54 pin LGA
Dimension	17.0 × 22.0 × 2.6 mm
Weight	1.88±0.03g

Environmental Specifications

Working Temperature	-40°C~+85°C
Storage Temperature	-55°C~+95°C
Humidity	95% No condensation
Vibration	GJB150.16A-2009, MIL-STD-810F
Shock	GJB150.18A-2009, MIL-STD-810F

Communication Interface

3 × UART (LVTTL)
1 × I2C*
1 × SPI*
1 × CAN* (shared with UART3)

Note: Items marked with * are only supported by specific firmware.

Features

- » Based on the new generation GNSS SoC - NebulasIV, which integrates RF, baseband, and high precision algorithm
- » 17.0 x 22.0 x 2.6 mm SMD
- » Supports on-chip RTK positioning calculation on all systems and multiple frequencies
- » Supports BDS B1I/B2I/B3I/B1C/B2a/ B2b*, GPS L1/L2/L5, GLONASS G1/G2/G3*, Galileo E1/E5a/E5b/E6*, QZSS L1/L2/L5, SBAS
- » All-system multi-frequency RTK engine and advanced RTK technology
- » Independent tracking of different frequencies and 60dB narrowband anti-jamming technology

UM980 is Unicore's new-generation proprietary high-precision RTK positioning module. Combining advanced hardware design and exclusive algorithms, UM980 supports BDS B1I/B2I/B3I/B1C/B2a/B2b*, GPS L1/L2/L5, GLONASS G1/G2/G3*, Galileo E1/E5a/E5b/E6*, QZSS L1/L2/L5, and SBAS. The built-in multi-frequency anti-jamming technology enhances RTK calculation on multiple modes and frequencies, which significantly improves RTK initialization speed, measurement accuracy and reliability in complex environments such as city blocks and tree shades. Relying on the excellent performance, UM980 is well suited for high-precision navigation and positioning applications such as UAV, lawn mower, precision agriculture, surveying and mapping and intelligent driving.

Basic Information

Channel	1408 channels, based on NebulasIV			
Frequency	BDS B1I/B2I/B3I/B1C/B2a/B2b* GPS L1C/A/L1C*/L2P (Y)/L2C/L5 GLONASS G1/G2/G3* Galileo E1/E5a/E5b/E6* QZSS L1/L2/L5			
Single Point Positioning(RMS)	Horizontal: 1.5m	Time Accuracy(RMS)	20 ns	
	Vertical: 2.5m	Velocity Accuracy (RMS)	0.03 m/s	
DGPS (RMS)	Horizontal: 0.4m	Cold start	<30s	
	Vertical: 0.8m	Initialization Time	<5s (typical)	
RTK (RMS)	Horizontal: 0.8cm+1ppm	Initialization Reliability	>99.9%	
	Vertical: 1.5cm+1ppm	Data Update Rate	50Hz* Positioning	
Observation Accuracy (RMS)	BDS	GPS	GLONASS	Galileo
B1I/B1C/L1C*/L1C/A/G1/E1 Code	10cm	10cm	10cm	10cm
B1I/B1C/L1C*/L1C/A/G1/E1 Carrier Phase	1mm	1mm	1mm	1mm
B2I/B2a/B2b*/L5/E5a/E5b Code	10cm	10cm	10cm	10cm
B2I/B2a/B2b*/L5/E5a/E5b Carrier Phase	1mm	1mm	1mm	1mm
B3I/L2P(Y)/L2C/G2 Code	10cm	10cm	10cm	10cm
B3I/L2P(Y)/L2C/G2 Carrier Phase	1mm	1mm	1mm	1mm
Differential Data	RTCM V3.X			
Data Format	NMEA-0183, Unicore			